

certificate of conformity

OMS-Konformitätsbescheinigung

OG-4467CU0432

Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	smart metering components <i>Smart-Metering Komponenten</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Techem Energy Services GmbH Hauptstraße 89, D-65760 Eschborn
Distributor <i>Vertreiber</i>	Techem Energy Services GmbH Hauptstraße 89, D-65760 Eschborn
Product Category <i>Produktart</i>	OMS-components: Wireless M-Bus (4467)
Product Description <i>Produktbezeichnung</i>	OMS-interface for a heat meter
Model <i>Modell</i>	vario 4 Typ 4.1.1
Test Reports <i>Prüfberichte</i>	type testing: 19-00066-307 from 16.12.2019 (EBI)
Test Basis <i>Prüfgrundlagen</i>	DVGW G 5484 (01.09.2016) DVGW CERT ZP 4400 (13.12.2017)
Date of Expiry / File No. <i>Ablaufdatum / AZ</i>	16.12.2024 / 20-0024-GOE

70028-04-A-DE

23.01.2020 Kö A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 for certification of products for energy and water supply industry.

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte Stelle für die Zertifizierung von Produkten der Energie- und Wasserversorgung.



DVGW CERT GmbH
Zertifizierungsstelle
Josef-Wirmer-Str. 1-3
53123 Bonn
Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993
www.dvgw-cert.com
info@dvgw-cert.com

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
vario 4 Type 4.1.1	OMS-interface: C1 Protocol: M-Bus Transmission frequency: 868,95	

Hints of Utilization / Remarks***Verwendungshinweise / Bemerkungen***

The meter and the measuring unit were not part of the type examination.

The test refers solely to the test of the M-Bus according to the OMS-CT Generation 4 (2016); Open Metering Conformance Test; Volume 1-4.

Device type: 0x04; heat; version: 0x28

OMS interface: C1

Frequency: 868.95 MHz

Encryption mode: 7

Transmission rate: 240 s

Installation telegram: no

Static telegram: no

Load profile: yes

Temperature range: 0 ° C ... +80 ° C

Application class: HT

Power supply: lithium battery 3V

RED (2014/53/EU): self declaration of Techem Energy Service GmbH and the manufacturer Diehl Metering GmbH (TR-68612-13285-01 vom 22.06.2017)