



CERT

certificate of conformity

OMS-Konformitätsbescheinigung

OG-4467CT0509

Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	smart metering components <i>Smart-Metering Komponenten</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Sensus GmbH Ludwigshafen Industriestraße 16, D-67063 Ludwigshafen
Distributor <i>Vertreiber</i>	Sensus GmbH Ludwigshafen Industriestraße 16, D-67063 Ludwigshafen
Product Category <i>Produktart</i>	OMS-components: Wireless M-Bus (4467)
Product Description <i>Produktbezeichnung</i>	OMS interface for heat meters
Model <i>Modell</i>	PolluCom F Wireless M-Bus
Test Reports <i>Prüfberichte</i>	supplement test: 21-00526-AB01-288 from 19.11.2021 (EBI)
Test Basis <i>Prüfgrundlagen</i>	DVGW CERT ZP 4400 (13.12.2017) DVGW G 5484 (01.09.2016)
Date of Expiry / File No. <i>Ablaufdatum / AZ</i>	19.10.2023 / 21-0691-GOR

70209-04-A-DE

28.01.2022 K6 A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle



DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
PolluCom F Wireless M-Bus	Protocol: M-Bus Transmission frequency: 868,95 MHz	

Hints of Utilization / Remarks**Verwendungshinweise / Bemerkungen**

The meter and the measuring unit were not part of the type examination.

The test refers solely to the test of the M-Bus according to the OMS-CT Generation 4 (2016); Open Metering Conformance Test; Volume 1-4.

Device type: 0x04, heat

Version: 0x1D

OMS interface: T1, C1 (short and long telegram)

Frequency: 868.95 MHz

Encryption mode: 5

Security profile: A

Transmission rate: 16 s

Installation telegram: no

Static telegram: no

Load profile: no

Temperature range: -20 ° C ... +65 ° C

Application class: HT

Power supply: battery

R & TTE approval: CTC Advanced GmbH, 1-5382/17-01-02-A; 1-5382/17-01-03; 1-5382/17-01-04-B, Saarbrücken

The test refers solely to the test of the M-Bus according to the OMS-CT Generation 4 (2016 and 2020); Open Metering Conformance Test; Volume 1-4.

Device type: 0x04, heat

Version: 0x1D

OMS interface: T1, C1 (short and long telegram)

Frequency: 868.95 MHz

Encryption mode: 7

Security profile: B

Transmission rate: 16 s

Installation telegram: no

Static telegram: no

Load profile: no

Temperature range: -15 ° C ... +65 ° C

Application class: HT

Power supply: battery

R & TTE approval: CTC Advanced GmbH, 1-5382/17-01-02-A; 1-5382/17-01-03; 1-5382/17-01-04-B, Saarbrücken